

High Performance Lights

Sunshine Coast

www.asllights.com.au



LED Simulated Rotating Beacons

Superior LED Technology SAE Class 2 Rated OUTPUT

Series 7

- 10-40v
- 24 x 3watt AMBER LEDs
- 1.2 amp draw @ 12v
- amber polycarbonate lens
- 160 RPM
- 162 diam x 176mm height (alloy)
- encapsulated electronics
- ABS or diecast aluminium base
- mounting O-ring seals
- maximum ambient operating temperature 50deg c.
- 2 year warranty
- also available in RED, GREEN or BLUE
- **122 Part No ASL-SRBMs07A (suction magnetic base)**
- **123 Part No ASL-SRB07-ALU (alloy base)**

alloy base



Series 4

- 10 – 40 v
- 8 x 3watt AMBER LEDs
- 0.7 amp draw @ 12 v
- amber polycarbonate lens
- 160 RPM
- 162 diam x height 117mm (alloy) 125mm (ABS)
- encapsulated electronics
- ABS or diecast aluminium base
- mounting & O – ring seals
- maximum ambient operating temperature 50 deg c
- 2 year warranty
- also available in RED, GREEN or BLUE

126 Part No: SRBM04A (magnetic flange base)



127 Part No: SRBMS04A (magnetic alloy suction base)



124 Part No ASL-SRB04A (ABS flange base)



125 Part No ASL-SRB04A-ALU (alloy base)

ASL-SRB 04 SERIES

- TRI MODE warning signal beacons with switchable pulsing (strobe) & simulated rotating patterns
- 8 x high intensity LEDs
- amber Polycarbonate lens
- Input voltage: DC 12-24v
- Current draw: 0.8A @ 12v (rotating) 96 rpm simulated rotating pattern SAE Class 2
- 1.5A @ 12v (strobe) 6 selectable pulsing (strobe) patterns SAE Class 1
- encapsulated electronics, 6 metre double insulated cable
- diecast aluminium base diameter 162mm x 117mm height overall
- ambient operating temperature range -25 to 55c

129 Part No: ASL-SRBMP-04A-ALU



